



HARWIN

HARDWARE

Coin Cell Battery Holders



COIN CELL BATTERY HOLDERS – FOR REPLACEABLE COIN CELLS



Motherboards and small remote devices use coin cells to provide a trickle charge keeping memory and internal clocks running, or to power low-level transmissions and simple functions. Often the design will just solder the coin cell to the PCB, but this limits the life of the device to the life on the battery. By adding a [simple holder to the PCB](#), batteries can be replaced in service.

APPLICATIONS



These compact holders provide the option to replace batteries and extend service life in a variety of applications across all markets and industries.

- Retail
- UAV
- IOT
- Robotics

SURFACE MOUNT, UNINSULATED



S8201-46R



S8211-46R


These holders are designed to be used with a negative contact zone underneath on the PCB – the holder is the positive contact. With 2 large contact fingers, a wide range of battery widths can be used, and they have a high retention force.

- [S8201-46R](#) – 12mm diameter coin cells: CR1220, CR1225, BR1220, BR1225
- [S8211-46R](#) – 20mm diameter coin cells: CR2016, CR2025, CR2032, BR2016, BR2020, BR2025 & similar

SURFACE MOUNT, INSULATED



S8411-45R



S8421-45R

The insulated holders accept the most popular size of Ø12 and Ø20mm batteries. They are more suitable for applications where an end user or consumer may be required to replace the battery. Both negative and positive contacts are built into the holder.

- [S8411-45R](#) – 12mm diameter coin cell CR1220
- [S8421-45R](#) – 20mm diameter coin cell CR2032

TAPE AND REEL PACKAGING



These four holders are all supplied in Tape-and-Reel packaging, making them ideal for automated assembly to the PCB. The holder designs incorporate flat areas for vacuum pick-and-place, so there are no disposable caps or film.

STRAIGHT THROUGHBOARD, INSULATED



S8401-46

The [S8401-46](#) is compatible with 20mm diameter coin cells CR2032 and BR2032. It provides the easiest access for battery replacement, and both positive and negative contacts are built into the design.

NOTE: Although these holders are supplied in a tape and reel packing style, they are not oriented for pick and place assembly – the packing style is used to provide the best protection to the throughboard terminations.

LEARN MORE ABOUT OUR OTHER RANGES



HIGH RELIABILITY
WITH SUPREME
PERFORMANCE



DEPENDABLE
CONNECTIVITY
ACROSS THE BOARD



INNOVATIVE
DESIGNS FOR
EASY ASSEMBLY

Find out more about our full range
of inter-connection solutions at

www.harwin.com

HRI
RANGE

BBi
RANGE

EZi
RANGE

GET HELP FROM A HARWIN EXPERT

Our experts are specialists in their field with many years of experience in their respective roles and industries.

Find an expert that can help you with your enquiry.

[Click Here >>](#)

CAD Models and Evaluation Samples also available at www.harwin.com



HARWIN

CONNECT TECHNOLOGY
WITH CONFIDENCE



E: support@harwin.com

WWW.HARWIN.COM