



N-Channel Enhancement Mode MOSFET


Features

- ◆ $V_{DSS} = 60V$
- ◆ $R_{DS(ON)} < 0.8m\Omega @ V_{GS} = 10V$
- ◆ Fully Avalanche Rated
- ◆ Pb Free & RoHS Compliant
- ◆ Isolation Type Package
- ◆ Electrically Isolation Base Plate

Preliminary



Dimensions in inches and (millimeters)



Applications

- ◆ Backlighting
- ◆ Battery Chargers
- ◆ Power Converters
- ◆ AC Motor Drivers
- ◆ Synchronous Rectifiers

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous @ $T_c = 25^\circ C$ @ $T_c = 100^\circ C$	I_D	660 500	A
Drain Current-Pulsed @ $T_c = 25^\circ C$	I_{DM}	1600	A
Maximum Power Dissipation	P_D	1500	W
Storage Temperature Range	T_{STG}	-50 to +150	°C
Operating Junction Temperature Range	T_J	-50 to +150	°C
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	0.08	°C/W
Isolation Voltage (Between All Terminals and Baseplate)	V_{iso}	2500	V
Mounting torque (M4 Screw)	To heatsink To terminals	1.3 1.1	Nm







	DIMENSIONS			
	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.460	0.483	11.68	12.28
B	0.307	0.323	7.80	8.20
C	0.030	0.033	0.75	0.85
D	0.071	0.081	1.80	2.05
E	1.488	1.504	37.80	38.20
F	1.248	1.260	31.70	32.00
G	0.917	0.957	23.30	24.30
H	0.996	1.008	25.30	25.60
I	0.579	0.602	14.70	15.30
J	0.492	0.516	12.50	13.10
K	0.161	0.169	4.10	4.30
L	0.161	0.169	4.10	4.30
M	0.181	0.197	4.60	5.00
N	0.165	0.181	4.20	4.60
O	1.181	1.197	30.00	30.40
Q	-0.002	0.004	-0.05	0.10
R	M4*8			

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
OFF Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_{DS}=0.1mA$	60	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{GS}=0V, V_{DS}=60V$	-	-	100	μA
Gate-Body Leakage	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	250	nA
ON Characteristics						
Gate Threshold Voltage	V_{TH}	$V_{DS}=V_{GS}, I_{DS}=8mA$	2.4	-	3.5	V
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_{DS}=100A$	-	0.6	0.8	m Ω
Gate Resistance	R_G		-	1.9	2.9	Ω
Forward Transconductance	g_{fs}	$V_{DS}=2.5V, I_D = 270A$ ^{Note1}	-	220	-	S
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{DS}=25V$	-	67600	-	pF
Output Capacitance	C_{oss}	$V_{GS}=0V$	-	5400	-	
Reverse Transfer Capacitance	C_{rss}	Freq.=1MHz	-	1600	-	
Switching Characteristics						
Turn-On Delay Time	$t_{d(on)}$	$V_{DS}=0.5V$ $V_{GS}=10V$ $I_{DS}=100A$	-	95	-	ns
Rise Time	t_r		-	330	-	
Turn-Off Delay Time	$t_{d(off)}$		-	350	-	
Fall Time	t_f		-	420	-	
Total Gate Charge at 10V	Q_g	$V_{DS}=30V$	-	980	-	nC
Gate to Source Charge	Q_{gs}	$V_{GS}=10V$	-	210	-	
Gate to Drain Charge	Q_{gd}	$I_{DS}=100A$	-	411	-	
Reverse Diode Characteristics						
Drain-Source Diode Forward Voltage	V_F	$T_J = 25^\circ\text{C}, I_F = 300A$	-	-	0.95	V
Diode Continuous Forward Current	I_F		-	-	500	A
Diode Pulsed Current ^{Note1}	$I_{F,pulse}$		-	-	1600	A
Reverse Recovery time	T_{RR}	$I_F=0.5V, I_R=1.0A, I_{RR}=0.25A$	-	-	530	ns


Notes:

 1. Pulse Test: Pulse Width $\leq 300 \mu s$, Duty Cycle $> 2\%$.


Typical Characteristics
Fig 1. Power dissipation

Fig 2. Drain current

Fig 3. Safe operating area

Fig 4. Maximum Transient Thermal Impedance

Fig 5. Typ. output characteristics

Fig 6. Typ. drain-source on resistance


Typical Characteristics
Fig 7. Typ. transfer characteristics


$$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}; \text{parameter: } T_j$$


Fig 8. Typ. forward transconductance


$$g_{fs} = f(I_D); T_j = 25^\circ\text{C}$$


Fig 9. Drain-source on-state resistance



$$R_{DS(on)} = f(T_j); I_D = 150\text{A}; V_{GS} = 10\text{V}$$







Fig 10. Typ. gate threshold voltage

$$V_{GS(th)} = f(T_j); V_{GS} = V_{DS}; \text{parameter: } I_D$$


Fig 11. Typ. capacitances

$$C = f(V_{DS}); V_{GS} = 0\text{V}; f = 1\text{MHz}$$


Fig 12. Typical forward characteristics of reverse diode


Typical Characteristics
Fig 13. Forward derating curve of reverse diode

Fig 14. Peak forward surge current of reverse diode

Fig 15. Typical reverse diode characteristics

Fig 16. Typ. gate charge
 $V_{GS} = f(Q_{gate}); I_D = 100\text{A}$ pulsed; parameter: V_{DD}

Fig 17. Gate charge waveforms


Disclaimer

DACO Semiconductor reserves the right to make modifications, enhancements, improvements, corrections, or other changes to this document and any product described herein without prior notice. For the most up-to-date version, please visit our website.

DACO Semiconductor makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does DACO Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any liability, including without limitation special, consequential or incidental damages.

Purchasers are responsible for its products and applications using DACO Semiconductor products, including compliance with all laws, regulations, and safety requirements or standards, regardless of any support or application information provided by DACO Semiconductor. "Typical" parameters that may be provided in DACO Semiconductor datasheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typical" must be validated for each customer application by the customer's technical experts.

DACO Semiconductor products are not designed, authorized, or warranted to be suitable for use in life support, life-critical or safety-critical systems, or equipment, nor in applications where failure or malfunction of DACO Semiconductor's product can reasonably be expected to result in personal injury, death or severe property or environmental damage. DACO Semiconductor accepts no liability for the inclusion and/or use of DACO Semiconductor's products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Purchasers who buy or use DACO Semiconductor products for any unintended or unauthorized applications are required to indemnify and absolve DACO Semiconductor, its suppliers, and distributors from any claims, costs, damages, expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that DACO Semiconductor was negligent regarding the design or manufacture of the part.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or by any information storage and retrieval system, or otherwise, without the prior written permission of DACO Semiconductor Co., Ltd.