

Material Composition for M22-6013005

Product Information	
Part Number:	M22-6013005
Part Description:	2mm pitch PC/104 Plus Skt
Part Weight (g):	9.422

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact - Phosphor Bronze	3.81	5%	Copper	7440-50-8
	0.201	1%	Tin	7440-31-5
	0.0078	0.5%	Phosphorus	7723-14-0
	0	0.00804g max	Nickel (impurity only)	7440-02-0
	0	0.00804g max	Zinc (impurity only)	7440-66-6
	0	0.00396g max	Iron (impurity only)	7439-89-6
	0	0.00084g max	Lead (impurity only)	7439-92-1
Contact - Plating	0	0.00804g max	Other Impurities	
	0.0664	10%	Nickel	7440-02-0
	0.0072	30%	Gold	7440-57-5
Moulding (total weight)	5.33	5%	30% GF Nylon 6T	
Containing:	2.665	5%	Nylon 6T	63428-83-1
	1.599	5%	30% Glass Fibre	65997-17-3
	0.2665	5%	Antimony Trioxide	1309-64-4
	0.8	5%	Other Brominated Flame Retardants [ISO 1043-4 Code No: FR(17)]	

Prepared by:

M. J. Perry

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

HARWIN